Vision HFR Forklift 3-Camera System

AI HUMAN-FORM RECOGNITION, 3 CAMERAS · FORKLIFTS

PART No. SL-0010-PS

An AI human-form-recognition safety system that detects people — not general movement — across three blind-spot zones and warns the operator before a strike. Designed for larger forklifts and industrial vehicles.

- AI human-form recognition across three blind-spot zones
- Escalating visual and audible in-cab alert
- Speed-gated for low-speed manoeuvring
- IP69K cameras with WDR and infrared
- Shock- and vibration-proof, rated –30 to +70 °C



AI human-form recognition · for professional installation

PRODUCT MARKINGS CE

HFR AI PEOPLE, NOT MOTION	**3 cameras** 3 BLIND-SPOT ZONES	**Escalating** VISUAL + AUDIBLE	**IP69K** WDR + INFRARED
Speed-gated LOW-SPEED WORK	**–30 to +70 °C** OPERATING RANGE	**Shock-proof** VIBRATION-PROOF	**Professional** INSTALLATION

Ideal for

Forklifts · Warehouses · Docks & yards · Industrial vehicles

People, not motion
AI recognises human forms to cut false alarms.

Escalating warnings
Visual and audible in-cab alerts as risk increases.

Built for site life
IP69K cameras for day, night and poor weather.

Why Vision Telematics

Expert support Help from our specialist team

Commercial grade Built for working fleets and assets

One platform Vehicles, cameras & assets, one login

One partner Hardware, connectivity & software

Features & benefits

FEATURE — WHAT IT DOES	BENEFIT — WHAT IT MEANS FOR YOU
Human-form recognition AI recognises people rather than racking, pallets or general movement.	**Fewer nuisance alarms** Operators trust the alerts — and act on them.
Escalating in-cab alert Visual and audible warnings that escalate as a person gets closer.	**Time to react** Clear warning before a strike, not after.
Speed-gated activation Detection active during low-speed manoeuvring.	**Alerts when they matter** No distraction at travel speed.
IP69K cameras with WDR & IR Sealed cameras with wide dynamic range and infrared.	**Works day and night** Reliable detection in rain, dust and darkness.

Technical specification

System specification

Detection	AI human-form recognition (HFR)
Cameras	3 × IP69K camera with WDR and infrared
Coverage	three blind-spot zones
Alerts	Escalating visual and audible in-cab warning
Activation	Speed-gated for low-speed manoeuvring
Operating temperature	–30 °C to +70 °C
Durability	Shock- and vibration-proof
Certifications	CE

Options & accessories

Options & accessories

SL-0014-PS	Red-line zonal truck light	SL-0027-PS	Thumbs-up / no-entry LED display
SL-0015-PS	Red LED zonal light	SL-0028-PS	Two-way switch panel

Ready to put the Vision HFR Forklift 3-Camera System to work?

Talk to our team for a demonstration, a tailored quotation or help choosing the right configuration. We supply and support everything — hardware, connectivity and the Vision platform — from one partner.

Book a demo | Request a quote

Scan for the product page

CALL
0800 020 9339

EMAIL
info@visiontelematics.com

WEB
visiontelematics.com

VISIT
22 High Street, Epworth, Doncaster DN9 1ET, UK

Vision Telematics Limited · Registered in England & Wales No. 15637894 · VAT No. GB 466 8495 33 · 22 High Street, Epworth, Doncaster, DN9 1ET, United Kingdom
© 2026 Vision Telematics Limited. All rights reserved. Specifications are subject to change without notice and may vary by region and configuration. Images are for illustration only. Vision Telematics accepts no responsibility for errors or omissions.