7" HD Monitor (quad, 4-channel)

7-INCH HD IPS IN-CAB MONITOR · 4 CAMERA INPUTS

PART No. SL-0015-SC

A 7-inch HD IPS in-cab monitor with 4 camera inputs and an integrated sunshade, giving drivers a clear view of all four cameras at once, with quad, triple, dual and single layouts.

- 7-inch HD IPS display, 700 cd/m²
- 4 camera inputs — 1080p, 720p, CVBS or mixed
- Quad, triple, dual or single views
- 3 trigger inputs with adjustable delay
- Wide 12–36 V supply; –20 °C to +70 °C



7-inch HD IPS with integrated sunshade

PRODUCT MARKINGS CE

7" IPS	4 inputs	700 cd/m²	12–36 V
HD DISPLAY	1080P / 720P / CVBS	BRIGHTNESS	WIDE INPUT

Ideal for

- HGVs
- Buses & coaches
- Refuse vehicles
- Plant & machinery

See the blind spots
Live camera views where the driver needs them.

Readable in sunlight
Bright IPS panel with integrated sunshade.

Easy to fit
U-bracket and fan-bracket included.

Why Vision Telematics

Expert support
Help from our specialist team

Commercial grade
Built for working fleets and assets

One platform
Vehicles, cameras & assets, one login

One partner
Hardware, connectivity & software

Options & accessories

Options & accessories

SL-0009-SC	Side camera (IR), 1080p, IP69K	SL-0011-SC	Mini dome camera (IR), 1080p
SL-0010-SC	Rear camera (IR), 1080p, IP69K	SL-0004-SC	Vision AI MDVR 8

Features & benefits

FEATURE — WHAT IT DOES	BENEFIT — WHAT IT MEANS FOR YOU
Multi-camera viewing Quad, triple, dual or single layouts with mirror/normal per channel.	**Full awareness for the driver** Safer manoeuvring around people and obstacles.
Bright IPS display 700 cd/m² with auto-dimming and day/night brightness.	**Clear in any light** Easy to read in bright sun and at night.
Wide-voltage supply 12–36 V for cars, vans and HGVs.	**One monitor, any vehicle** Simplifies stock and installs.

Technical specification

Monitor specification

Display	7-inch HD IPS
Brightness	700 cd/m²
Inputs	4 × camera (1080p / 720p / CVBS / mixed)
Display modes	Quad, triple, dual or single views
Triggers	3 × trigger inputs with adjustable delay
Controls	OSD menu, remote control, auto dimming
Supply	12–36 V DC
Operating temperature	–20 °C to +70 °C
Included	Sunshade, U-bracket and fan-bracket
Certifications	CE

Ready to put the 7″ HD Monitor (quad, 4-channel) to work?

Talk to our team for a demonstration, a tailored quotation or help choosing the right configuration. We supply and support everything — hardware, connectivity and the Vision platform — from one partner.

Book a demo | Request a quote

Scan for the product page

CALL
0800 020 9339

EMAIL
info@visiontelematics.com

WEB
visiontelematics.com

VISIT
22 High Street, Epworth, Doncaster DN9 1ET, UK

Vision Telematics Limited · Registered in England & Wales No. 15637894 · VAT No. GB 466 8495 33 · 22 High Street, Epworth, Doncaster, DN9 1ET, United Kingdom
© 2026 Vision Telematics Limited. All rights reserved. Specifications are subject to change without notice and may vary by region and configuration. Images are for illustration only. Vision Telematics accepts no responsibility for errors or omissions.