Vision Track Cellular

RUGGED TWO-WAY LTE-M TRACKER · STANDARD BUILD

PART No. SL-0003-GF

Rugged LTE-M cellular asset tracker for non-powered assets with two-way communication and up to 10-year battery life — standard, non-hazardous-area build. Certification schedules and the full specification are available on request.

- Two-way LTE-M / NB-IoT communication — settings changed over the air
- Up to 10-year battery life at one message per day
- IP68 and IP69K sealed against dust, immersion and high-pressure wash
- Rugged housing with integrated mounting points for bolt or band fixing
- Lowest cost per asset across the hazardous-area device family



Standard build · non-hazardous areas

PRODUCT MARKINGS CE

Standard build — NON-HAZARDOUS AREAS
LTE-M / NB-IoT — CONNECTIVITY
Up to 10 yrs* — PRIMARY BATTERY
IP68 · IP69K — SEALED
–40 to +65 °C — OPERATING RANGE*
Bolt or band — MOUNTING
Two-way — OTA SETTINGS
Set & forget — LONG SERVICE LIFE

Ideal for

- Remote equipment
- Containers
- Generators
- Trailers
- Tanks
- Rental equipment

Ex-ready family
The same family as our Zone 0 trackers.

Coverage anywhere
Satellite, cellular or both.

Years of service
Long-life power with no wiring.

Why Vision Telematics

Expert support
Help from our specialist team

Professional installation
Installed by trained technicians

One platform
Vehicles, cameras & assets, one login

One partner
Hardware, connectivity & software

Features & benefits

FEATURE — WHAT IT DOES	BENEFIT — WHAT IT MEANS FOR YOU
Rugged standard build The same rugged housing, for sites without explosive atmospheres.	**Lower cost where Ex is not needed** Ideal for heavy equipment and remote assets.
LTE-M / NB-IoT connectivity Two-way low-power cellular — settings changed over the air.	**Coverage where you need it** Choose the network to match the site, from city depots to offshore.
Long-life primary battery 8–10 years at one message per day.	**Set and forget** Years of service without site visits.
IP68 & IP69K sealing Sealed against dust, immersion and high-pressure wash.	**Survives the harshest sites** Built for oil, gas, chemical and offshore environments.

Technical specifications

Specification

Hazardous-area rating	Standard build — not certified for hazardous areas
Connectivity	LTE-M / NB-IoT
Power	Primary battery
Service life	Up to 10 yrs (depending on reporting)
Ingress protection	IP68 and IP69K
Mounting	Integrated mounting points for bolt or band fixing
Certifications	CE

Options & accessories

Options & accessories

SL-0001-GF	Vision Track Satellite	SL-0004-GF	Vision Zone Cellular
SL-0002-GF	Vision Zone Satellite	SL-0005-GF	Vision Zone Solar Satellite

On the Vision platform

Live location & history
Every asset on the same map as your vehicles.

Movement & tamper alerts
After-hours movement and removal flagged instantly.

Geofences
Alerts as kit enters or leaves yards and sites.

Utilization reports
See what moved, what sat idle and for how long.

* Service life and operating figures depend on reporting interval and configuration. Certification schedules available on request.

Ready to put the Vision Track Cellular to work?

Talk to our team for a demo, a tailored quote or help choosing the right configuration. We supply, install and support everything — hardware, connectivity and the Vision platform — from one partner.

Book a demo

Request a quote

Scan for the product page

CALL
0800 020 9339

EMAIL
info@visiontelematics.com

WEB
visiontelematics.com

VISIT
22 High Street, Epworth, Doncaster DN9 1ET, UK

Vision Telematics Limited · Registered in England & Wales No. 15637894 · VAT No. GB 466 8495 33 · 22 High Street, Epworth, Doncaster, DN9 1ET, United Kingdom
© 2026 Vision Telematics Limited. All rights reserved. Specifications are subject to change without notice and may vary by region and configuration. Images are for illustration only. Vision Telematics accepts no responsibility for errors or omissions.